



ITT

BCPT

Residential Water Systems

CentriPro

T Series

Epoxy Coated Diaphragm Tanks




Stand Model
(Vertical)



In-Line Pipe Mounted
Model

FEATURES

- **Deep Drawn Steel Shells:** provide maximum material strength.
- **Inner Shell:** Prevents diaphragm from over-expanding.
- **Heavy Duty Diaphragm:** Made of finest quality butyl rubber. Separates air and water, maintains air change.
- **Interior Tank Lining:** Tank features a durable fusion bonded polymeric lining. Meets FDA requirements.
- **Maximum Working Pressure:** 100 PSI.
- **Temperature Rating:** Maximum 120° F.
- **Epoxy Coated System Connection:** On all stand and in-line models.
- **Appliance Appearance Exterior Finish:** Tan color, high durability exterior finish of tough, powder coat over a zinc phosphate surface treatment.
- Tanks are designed for installation indoors or where they are protected from rain, irrigation overspray, salt air and other corrosive environments. Always protect tanks from freezing.
- **Heavy Duty High Density polypropylene Base:** Eliminates corrosion due to condensation and exposure to the elements.
- **Tanks have a 5-year limited warranty. See instruction manual for complete warranty details.**



CentriPro®

CentriPro is a brand of ITT Corporation.

www.centripro.com

Engineered for life



Certified to ANSI/NSF 61



ITT

Residential Water Systems

	Model No.	Total Volume (Gals.)	Drawdown in Gals. at System Operating Pressure Range of			Max. Drawdown Vol. (Gals.)	Pre-Charge PSI	System Connection	Dimensions		Shipping Weight	Height From Floor to Center of Base Opening
			20/40 PSIG	30/50 PSIG	40/60 PSIG				Diameter	Height		
Stand Models	T45	13.9	5.1	4.3	3.7	8.4	38	1" NPTF	15 ³ / ₈	24 ¹⁵ / ₁₆	24	3 ³ / ₈
	T60	19.9	7.3	6.1	5.3	12.1	38	1" NPTF	15 ³ / ₈	32 ³ / ₈	34	
	T80	25.9	8.9	7.7	6.7	13.9	38	1" NPTF	15 ³ / ₈	39 ⁹ / ₁₆	43	
	T100	31.8	11.8	9.9	8.6	13.8	38	1" NPTF	15 ³ / ₈	47 ¹ / ₄	52	
	T140	45.2	16.5	13.9	12.1	27.3	38	1 ¹ / ₄ " NPTF	22	36 ⁹ / ₁₆	64	3 ³ / ₈
	T200	65.1	23.9	20.0	17.4	39.3	38	1 ¹ / ₄ " NPTF	22	48 ⁹ / ₁₆	89	
	T250	83.5	30.9	25.9	22.5	50.8	38	1 ¹ / ₄ " NPTF	26	46	116	3 ¹ / ₂
	T260	84.9	31.2	26.2	22.8	44.7	38	1 ¹ / ₄ " NPTF	22	60 ¹¹ / ₁₆	113	3 ³ / ₈
T350	115.9	42.9	35.9	31.3	70.5	38	1 ¹ / ₄ " NPTF	26	61 ⁵ / ₁₆	161	3 ¹ / ₂	
In-Line Models	T15P	4.5	1.7	1.4	1.2	2.7	38	3/4" NPTM	11	13 ¹⁵ / ₁₆	12	
	T25P	8.2	3.1	2.6	2.2	4.5	38	3/4" NPTM	11	23 ¹ / ₁₆	21	
	T45P	13.9	5.1	4.3	3.7	8.4	38	1" NPTM	15 ³ / ₈	21 ¹ / ₁₆	24	

NOTES:

P = Pipe Connection

(All dimensions are in inches and weight in lbs. Do not use for construction purposes.)

ACCESSORIES



AW39T Bracket:
Universal pump mounting bracket for use on all tan stand model tanks.

Order No.	Description	Wt. (lbs.)
AW39T	Universal Jet Pump Bracket - Tan	2



CentriPro and the ITT Engineered Blocks Symbol are registered trademarks and tradenames of ITT Corporation.

SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE.

BCPT October, 2008
Copyright (c) 2008 ITT Corporation

Engineered for life