



Irritrol's new I-PRO[™] Series spray heads combine a pressure-activated wiper seal and advanced formula lubricant that virtually eliminates troublesome stick ups. Add a unique tapered lip design that prevents debris from entering the body and you have a spray head with superior performance. It's rugged and reliable with a textured body style for a non-slip grip and even easier installation. I-PRO offers both a 4" and 6" replacement spray head that allows a complete retrofit without having to purchase the body – it even fits the Rain Bird[®] 1804 and 1806 spray head. Available in four pop-up heights with side inlet, pressure regulation and check valve options, the I-PRO Series fits most landscape applications. Irritrol. Get more done.

3", 4", 6" AND 12" MODELS

SPRAYS WELL WITH OTHERS.

KEY FEATURES & BENEFITS

PRESSURE-ACTIVATED SEAL WITH LUBRICANT ADDITIVE

Cleans debris from stem, reduces flow-by during pop-up and prevents leaking between cap and body. Extra lubricant additive further eliminates stick-ups

PRE-INSTALLED IN-RISER PRESSURE REGULATOR (OPTIONAL)

Maintains optimum nozzle performance at 30 psi and eliminates misting in varying pressure applications

PRE-INSTALLED CHECK VALVE (OPTIONAL) Prevents low-head drainage, eliminating flood or erosion damage by keeping water in lateral pipes in elevation changes up to 13'

RETROFITTABLE RISER Fits Rain Bird® 1800® Series body

STURDY AND ROBUST, TEXTURED BODY Provides for easy installation with a non-slip grip

SIDE AND BOTTOM INLETS ON 6" AND 12" MODELS (6" ALSO AVAILABLE IN NON-SIDE INLET) Reduces installation time

HEAVY-DUTY, STAINLESS STEEL RETRACTION SPRING Ensures positive pop-down

MALE-THREADED RISER Compatible with any female-threaded nozzle in the industry

PRE-INSTALLED FLUSH PLUG Makes system flushing a breeze and allows for easy nozzle installation

RATCHETING RISER

Two-piece mechanism permits easy arc adjustment in the field while sprinkler is operating



SPECIFICATIONS

- Inlet size: 1/2" female NPT threads
- Exposed diameter: 2 1/4"
- Body diameter: 1 ⁵/₈"
- Body height:
 - I-PRO300: 4 7/8"
 - I-PRO400: 5 %"
 - I-PRO600: 9 1/4"
 - I-PRO1200-SI: 16"
- Side inlet: 4 3/8" from center of side inlet to top of cap
- Recommended working pressure:
 - Standard: 20-50 psi (max 75 psi)
 - CV: 25-50 psi (max 75 psi)
 - PR: 30-70 psi (max 75 psi)
- Precipitation rate:
 - 0.96 4.69 inches per hour
 - Spacing: 4' 15'
 - Flow-by: 0 at 10 psi or greater; .1 GPM otherwise
- Five-year warranty

OPTIONAL ACCESSORIES

- Recycled-water indicator cap (I-PRO-NPC)
- Field-installable check valve (I-PRO-CV)






SPECIFYING INFORMATION

	 - XX-XXXX
NO	

OD		HEIGHT	SIDE INLET	OPTIONS	
PRO	- I-PRO pop-up spray head series	300 -3" 400 - 4" 400R - 4", less body 600 - 6" 600R - 6", less body 1200 - 12"	SI - Side inlet	CV - Pre-installed check valve PR - Pre-installed pressure regulator PR-CV - Pre-installed pressure regulator and check valve	
ample: An I-PRO Series sprinkler with a 6" pop-up height, side inlet, pressure regulation option and check valve = I-PRO600-SI-PR-CV					

SUPERIOR PERFORMING WIPER SEAL



Pressure-activated lip seal ensures a positive seal around the riser and reduces "flow-by" Lip creates positive seal to prevent body to cap leaks

REPLACEMENT SPRAY AVAILABLE (4" & 6" ONLY)

Why pay for a body you're just going to throw away? I-PRO offers a 4" and 6" replacement spray head that is everything but the body! Ideal for maintenance, this spray head also fits right in the can of the Rain Bird[®] 1804 & 1806 spray head for an easy retrofit. With features that are contractor-driven and field-proven, the I-PRO Series is sure to save you time and money.







Easily retrofits to Rain Bird 1800 Series

Remove the "guts" of 1806 spray head



COMPLETE FAMILY OFFERING

Available in four pop-up heights with side inlet, pressure regulation and check valve options, I-PRO is a spray series for most landscape applications.





I-P